

Great Industries Corp.

2021 Elm Court, Ontario, CA 91761 Tel: (909) 930-6322, Fax: (909) 930-6326 Email: greatsales@greatindustries.com

Material Safety Data Sheet

Section 1 Production and Company Identification

Product Name: Hook & Loop Fastening Tape

Product Description: 100% Nylon Material Hook & Loop

Manufacturer: Nam Liong Enterprise Co., Ltd. Taiwan

Section 2 Composition and Ingredient Information

Component	<u>%(W/W)</u>
Nylon 66	10~11%
Nylon 6	88~89%
Color Matter	< 0.2%
PU Glue	< 0.5%

Section 3 Physical and Chemical Properties

Physical Status: Solid

Apperance: Various Colors

Boiling Point: None

Melting Point: 265 ° C

Vapor Density: None

Vapor Pressure: None

Specific Gravity: 1.14

PH: 6.4

Water Solubility: Insoluble in water

Odor: None

Section 4 Special Fire and Explosion Hazard

Flash Point: None Explosive Limits: None

Extinguishing Media: Use water, regular dry chemical, carbon dioxide, regular foam

Extinguishing Procedure: extinguishing directly



Great Industries Corp.

2021 Elm Court, Ontario, CA 91761 Tel: (909) 930-6322, Fax: (909) 930-6326 Email: greatsales@greatindustries.com

Section 5 Stability and Reactivity

Stable under normal temperature and pressures Decomposed at high temperature

Section 6 First Aid Measures

Skin: Wash affected skin area with soap and water. If irritation develops, get medial attention

Ingestion: Help to vomit as much as possible and if illness or adverse symptoms develop, seek medical attention immediately.

Section 7 Handling and Storage

Handling: No risk to the health when handling at room temperature. Storage condition: Store away from heat of flames. Have good housekeeping to prevent dust accumulation.

Section 8 Exposure Control / Personal Protection

Ensure circulation of fresh air in working area.

Section 9 Toxicological information

Our series of products are certified by OEKO-TEX demands with AZO-FREE